

Section 3.1 : The Knapsack Problem

Knapsack

Input:

Knapsack with a capacity $B \in \mathbb{Z}^+$

Items $I = \{1, 2, \dots, n\}$

Item i has size $s_i \in \mathbb{Z}^+$ and value $v_i \in \mathbb{Z}^+$

Objective:

Find a set of items with total size $\leq B$ and largest possible total value

Greedy alg.:

Consider items in order of decreasing v/s -ratio

Does not have any constant approx. ratio:

Ex:

$$s_1 = v_1 = 1 \rightarrow v_1/s_1 = 1$$

$$s_2 = B, v_2 = B-1 \rightarrow v_2/s_2 = 1 - \frac{1}{B}$$

$$\text{Greedy} = 1$$

$$\text{OPT} = B-1$$

Dynamic prg alg: (Alg. 3.1)

$S:$

	0	1	...	i	n
0							
1							
v				x			
\vdots							
v_{total}							
	$\uparrow n$						
	$= \sum_{i=1}^n v_i$						

$s_{v,i}$: smallest possible total size of subset of items $1, \dots, i$ with total value v .

Ex: $B = 5$

	1	2	3
Size	2	4	2
Value	3	2	1

largest possible $\rightarrow 4$
total value $\leq B$

	0	1	2	3
0	0	0	0	0
1	∞	∞	∞	2
2	∞	∞	4	4
3	∞	2	2	2
4	∞	2	2	2
5	∞	∞	4	4
6	∞	∞	6	6
7	∞	∞	∞	8

What are the rules for filling the table?

$S:$	0	$i-1$	i	n
0	0	-	-	0
∞	-	-	-	-
$v - v_i$	-	X	-	-
v	-	X X	-	-
v_{total}	0	-	-	-

$S_{v,i}$: smallest possible total size of subset of items $1, \dots, i$ with total value v .

If $i=0$ and $1 \leq v \leq v_{\text{total}}$

$$S_{v,i} = \infty$$

Otherwise,

$$S_{v,i} = \begin{cases} 0, & \text{if } v=0 \\ S_{v,i-1}, & \text{if } 0 < v < v_i \\ \min \underbrace{\{S_{v,i-1}, S_{v-v_i, i-1} + s_i\}}_{\substack{\text{best solution} \\ \text{without item } i}}, & \text{if } v \geq v_i \end{cases}$$

How do we determine which items to select to obtain the optimal value?

i-1 i



include item i in the solution

i-1 i



leave out item i

Analysis of the alg:

Running time $O(nV_{\text{total}})$

Input size $O(\log B + n(\log M + \log S))$, where

$$M = \max_{1 \leq i \leq n} \{v_i\} \quad \text{and} \quad S = \max_{1 \leq i \leq n} \{s_i\}$$

Thus, the running time is not poly., since there could be instances with, e.g.,

$$V_{\text{total}} = 2^n \quad \text{and}$$

$$\log M + \log S = n$$

But if the numeric part of the input (i.e., the capacity, the item sizes, and the item values) were written in unary, the input size would be $\Theta(B + V_{\text{total}} + S_{\text{total}})$, and the running time would be poly. in the input size.

Hence, the running time is pseudo-polynomial.

Note: if V_{total} is poly. in n for all instances, the dyn prg. alg. is poly. leading to the following idea.

Idea for approx. alg.: Round values s.t. there are only a poly. number of different (equidistant) values:

- Choose a value μ .
- Round down each item value to the nearest multiple of μ .
- Do dyn. prg. on the rounded values

How to choose μ ?

- When rounding, each value loses less than μ . Hence, the value of any solution is changed by less than $n\mu$.
- $OPT \geq M = \max_{1 \leq i \leq n} \{v_i\}$.

Thus, if we want a precision of ϵ ,

$\mu = \frac{\epsilon M}{n}$ will do, since then

$$n\mu = \epsilon M \leq \epsilon \cdot OPT$$

(We will add more detail to this argument in the proof of Thm 3.5)

Since each rounded value is a multiple of μ , we may as well scale each value by a factor of $1/\mu$:

Alg 3.2

$$M \leftarrow \max_{1 \leq i \leq n} v_i$$

$$\mu \leftarrow \frac{\epsilon M}{n}$$

for $i \leftarrow 1$ to n

$$v'_i \leftarrow \left\lfloor \frac{v_i}{\mu} \right\rfloor$$

Do dyn. prg. with values v'_i (and sizes s_i)

Theorem 3.5

Alg. 3.2 is a $(1-\epsilon)$ -approx. alg. with a running time poly. in both input size and ϵ

Proof:

Approximation ratio:

For each item i , $\mu v'_i$ equals v_i rounded down to the nearest multiple of μ .

Let S be the set of items selected by Alg. 3.2. This is an optimal solution for the instance with values v'_i and hence also for the instance with values $\mu v'_i$.

Let O be the set of items in an optimal solution to the original instance with values v_i .

The total value produced by Alg. 3.2 is

$$\begin{aligned}
 \sum_{i \in S} v_i &\geq \sum_{i \in S} \underbrace{\mu v'_i}_{\substack{= v_i \text{ rounded down to nearest} \\ \text{multiple of } \mu}} \\
 &\geq \sum_{i \in S} \mu v'_i, \text{ since } S \text{ is optimal for} \\
 &\quad \text{rounded values} \\
 &> \sum_{i \in S} (\mu v'_i - \mu), \text{ since each item loses} \\
 &\quad \text{less than } \mu \text{ in the} \\
 &\quad \text{rounding} \\
 &\geq \sum_{i \in S} \mu v'_i - n\mu, \text{ since } |S| \leq n \\
 &= OPT - \varepsilon M \\
 &\geq (1-\varepsilon) OPT, \text{ since } OPT \geq M
 \end{aligned}$$

Running time:

$$\begin{aligned}
 \Downarrow \# \text{values} &= n \left\lfloor \frac{M}{\mu} \right\rfloor = n \left\lfloor \frac{n}{\varepsilon} \right\rfloor \leq n^2 \frac{1}{\varepsilon} \\
 \Downarrow \# \text{table entries} &\leq n^3 \cdot \frac{1}{\varepsilon} \\
 \Downarrow \text{Running time } O(n^3 \cdot \frac{1}{\varepsilon}) &
 \end{aligned}$$

□

According to Thm 3.5, Alg. 3.2 is a
fully polynomial time approximation scheme (FPTAS)
 also poly. in input size
 in $\frac{1}{\epsilon}$
 Family of A_ϵ } of alg., where A_ϵ has precision ϵ .
 ((1- ϵ)-approx. alg for max. problems,
 (1+ ϵ)-approx. alg for min. problems)

Def. 3.4 Def. 3.3

Thus, Thm 3.5 could also be stated like this:

Theorem 3.5: Alg 3.2 is a FPTAS

In the **Multiple Knapsack** problem, there are a fixed number of knapsacks.

Bin Packing can be seen as a dual problem of Multiple Knapsack:

In the **Bin Packing** problem, there is an unlimited supply of bins, all of size 1. The aim is to pack all items in as few bins as possible.

Simple approx. alg.s:

Next-fit (NF)

First-fit (FF)

Best-fit (BF)

Next-fit-Decreasing (NFD)

First-fit-Decreasing (FFD)

Best-fit-Decreasing (BFD)

Asymptotic approx. ratio

2

1.7

1.7

≈ 1.69

1.222...

1.222...

Approx. scheme?

Can we do the same kind of rounding for Bin Packing as we did for Knapsack?