

FF505
Computational Science

Lecture 1
Introduction to Matlab

Marco Chiarandini

Department of Mathematics & Computer Science
University of Southern Denmark

Outline

1. Course Organization
2. Getting Started
3. Solving Linear Systems

Outline

1. Course Organization
2. Getting Started
3. Solving Linear Systems

Organization

1. Introduction to mathematical tools (Claudio) – weeks 5-8
2. Tutorial on numerical software, MATLAB (Marco) – weeks 5-8
3. Laboratories on applications in physics (Paolo) – weeks 7-11

Evaluation

Group project during the laboratory session + oral exam

MATLAB Section

The MATLAB Section will cover

- MATLAB interactive environment
- MATLAB vectorized operations
- MATLAB programming
- data input/output
- simple visualization.

More specifically, it should prepare you to carry out the exercises from the theory and laboratory sections.

MATLAB Section – Schedule

- Schedule for weeks 5-8 (4 weeks):
 - Introduction, Friday, 12:15-14:00, Terminalrum or U140, (weeks 06-09)
 - Training:
 - S6, Thursday, 14-16, U24, (week 06-09)
 - S9, Tuesday, 14-16, U155, (weeks 06-09)

From week 9 you'll start also laboratories

- Communication tools
 - BlackBoard (BB)
(link to MATLAB Section <http://www.imada.sdu.dk/~marco/FF505>)
 - **Announcements** in BlackBoard
 - Personal email of instructors and Marco
 - Ask peers

Hands on Experience

Weekly exercises to be carried out in your study group before training sessions.

Slides and exercises sheets are posted after lecture at
<http://www.imada.sdu.dk/~marco/FF505>

Getting MATLAB


- machines in IMADA terminal room and in U26B (12 PCs)
(type `matlab` from command line)
- Remote connection (see note on web page)
- use a Matlab clone, eg, Octave
- wait for a license
- buy the student edition of Matlab: (ca. 600 DDK)
Link: http://www.mathworks.se/academia/student_version/
Then click on "BUY NOW"

MATLAB (**m**atrix **l**aboratory) is a [high-level language](#) and [interactive environment](#) to perform computationally intensive [numerical computations](#) faster than with low-level programming languages such as C, C++, and Fortran.

- Developed by a privately held company, MathWorks, 70% located at the company's headquarters in Massachusetts.
- Stable release: 2013b (we have 2012a)
- Written in C, Java
- License: Proprietary

Scientific vs Symbolic Computing

- **scientific computing** is based on numerical computation with approximate floating point numbers. $(-1)^s M 2^E$



http://www.mathworks.se/help/matlab/matlab_prog/floating-point-numbers.html

- **symbolic computation** manipulates mathematical expressions and other mathematical objects.
emphasis on exact computation with expressions containing variables that have not any given value and are thus manipulated as **symbols**

↪ Try <http://www.wolframalpha.com>

Symbolic computation can be done in MATLAB with the Symbolic Math Toolbox and the MuPAD editor (not installed)

Other similar numerical computing environments with high-level programming language are:

- Maple www.maplesoft.com (symbolic) – Proprietary
- Mathematica <http://www.wolfram.com/mathematica> (discrete mathematics) – [Proprietary]
- Octave www.gnu.org/software/octave – [General Public License]
- R www.r-project.org (statistics) – [GPL]
- Sage www.sagemath.org (discrete mathematics) – [GPL]
- SciPy www.scipy.org (based on python) – [GPL]
- ...
- later a comparison

Outline

1. Course Organization
2. Getting Started
3. Solving Linear Systems

MATLAB Desktop

- Command window
- Workspace
- Command history
- Current folder browser
- Variable editor
- MATLAB program editor
- Help
- Desktop menu
- Docking/Undocking, maximize by double click
- Current folder
- Search path (File menu -> set path)
- Documentation: Press ? → MATLAB → Getting Started

Command line programming

```
%%% elementary operations  
5+6  
3-2  
5*8  
1/2  
2^6  
1 == 2 % false  
1 ~= 2 % true. note, not "!="  
1 && 0  
1 || 0  
xor(1,0)
```

Variable Assignment

The = sign in MATLAB represents the **assignment** or **replacement** operator. It has a different meaning than in mathematics.

Compare:

$x = x + 3$ In math it implies $0=2$, which is an invalid statement
In MATLAB it adds 2 to the current value of the variable

```
%% variable assignment  
a = 3; % semicolon suppresses output  
b = 'hi';  
c = 3>=1;
```

% Displaying them:

```
a = pi  
disp(sprintf('2 decimals: %0.2f', a))  
disp(sprintf('6 decimals: %0.6f', a))  
format long % 16 decimal digits  
a  
format short % 4 decimal digits +  
scientific notation  
a
```

```
x + 2 = 20 % wrong statement  
x = 5 + y % wrong if y unassigned
```

Variables are visible in the **workspace**

Names:

- [a-z] [A-Z] [0-9] _
- case sensitive
- max 63 chars

Variable Editor

The screenshot shows the MATLAB Variable Editor and Command Window. The Variable Editor displays a 2x3 double matrix A with the following values:

	1	2	3	4
1	2	7	9	
2	4	2	5	
3				
4				

The Command Window shows the following commands:

```
>> x = 0:0.01:5;  
>> A = [2,7,9;4,2,5];  
fx >>
```

The Workspace window shows the following variables:

Name	Value	Min	Max
A	[2,7,9;4,2,5]	2	9
x	<1x501 double>	0	5

Managing the Work Session

```
who % lists variables currently in memory  
whos % lists current variables and sizes  
clear v % clear w/ no argt clears all  
edit filename % edit a script file  
clc % clears theCommand window  
... % ellipsis; continues a line  
help rand % returns help of a function  
quit % stops MATLAB
```

Predefined variables

```
pi  
Inf % 5/0  
NaN % 0/0  
eps % accuracy of computations  
i, j % imaginary unit  $i=j=\sqrt{-1}$   
3+8i % a complex number (no *)  
Complex(1,-2)
```


Working with Files

MATLAB handles three types of files:

- M-files `.m`: Function and program files
- MAT-files `.mat`: binary files with name and values of variables
- data file `.dat`: ASCII files

```
%% loading data
load q1y.dat
load q1x.dat
save hello v; % save variable v into file
hello.mat
save hello.txt v -ascii; % save as ascii
% fopen, fprintf, fscanf also work
% ls %% cd, pwd & other unix commands
work in matlab;
% to access shell, preface with "!"
```

Files are stored and searched in **current directory** and **search path**

Directories and paths

If we type `problem1`

1. seeks if it is a variable and displays its value
2. checks if it is one of its own programs and executes it
3. looks in the **current directory** for file `program1.m` and executes the file
4. looks in the search path for file `program1.m` and executes it

```
addpath dirname % adds the directory dirname to the search path
cd dirname % changes the current directory to dirname
dir % lists all files in the current directory
dir dirname % lists all files in dirname
path % displays the MATLAB search path
pathtool % starts the Set Path tool
pwd % displays the current directory
rmpath dirname % removes the directory dirname from the search path
what % lists MATLAB specific files in the current directory
what dirname % lists MATLAB specific files in dirname
which item % displays the path name of item
```

Getting Help

- `help funcname`: Displays in the Command window a description of the specified function `funcname`.
- `lookfor topic`: Looks for the string `topic` in the first comment line (the H1 line) of the HELP text of all M-files found on MATLABPATH (including private directories), and displays the H1 line for all files in which a match occurs.
Try: `lookfor imaginary`
- `doc funcname`: Opens the Help Browser to the reference page for the specified function `funcname`, providing a description, additional remarks, and examples.

1-D Arrays

Vectors: To create a row vector, separate the elements by commas. Use square brackets. For example,

```
>>p = [3,7,9]
p =
    3    7    9
```

You can create a column vector by using the transpose notation (').

```
>>p = [3,7,9]'  
p =
     3  
     7  
     9
```

You can also create a column vector by separating the elements by semicolons. For example,

```
>>g = [3;7;9]
g =
     3  
     7  
     9
```

Appending vectors:

```
r = [2,4,20];  
w = [9,-6,3];  
u = [r,w]  
u =  
    2    4   20    9   -6    3
```

```
r = [2,4,20];  
w = [9,-6,3];  
u = [r;w]  
u =  
    2    4   20  
    9   -6    3
```

Matrices: spaces or commas separate elements in different columns, whereas semicolons separate elements in different rows.

```
>> A = [2,4,10;16,3,7]
```

```
A =
```

```
    2  4 10  
   16  3  7
```

```
>>c = [a b]
```

```
c =
```

```
    1  3  5  7  9 11
```

```
>>D = [a ; b]
```

```
D =
```

```
    1  3  5  
    7  9 11
```

Arrays

Arrays are the basic data structures of MATLAB

Types of arrays:

numeric • character • logical • cell • structure • function handle

```
%% vectors and matrices
```

```
A = [1 2; 3 4; 5 6]
```

```
v = [1 2 3]
```

```
v = [1; 2; 3]
```

```
v = [1:0.1:2] % from 1 to 2, with stepsize of 0.1. Useful for plot axes
```

```
v = 1:6 % from 1 to 6, assumes stepsize of 1
```

```
C = 2*ones(2,3) % same as C = [2 2 2; 2 2 2]
```

```
w = ones(1,3) % 1x3 vector of ones
```

```
w = zeros(1,3)
```

```
w = rand(1,3) % drawn from a uniform distribution
```

```
w = randn(1,3) % drawn from a normal distribution (mean=0, var=1)
```

```
w = -6 + sqrt(10)*(randn(1,10000)) % (mean = 1, var = 2)
```

```
hist(w) % histogram
```

```
e = []; % empty vector
```

```
I = eye(4) % 4x4 identity matrix
```

```
A = linspace(5,8,31) % equivalent to 5:0.1:8
```

Indexing

```

%% indexing
A(3,2) % indexing is (row,col)
A(2,:) % get the 2nd row. %% ":" means every elt along that dimension
A(:,2) % get the 2nd col
A(1,end) % 1st row, last elt. Indexing starts from 1.
A(end,:) % last row

A([1 3],:) = [] % deletes 1st and 3rd rows
A(:,2) = [10 11 12]' % change second column
A = [A, [100; 101; 102]]; % append column vec
% A = [ones(size(A,1),1), A]; % e.g bias term in linear regression
A(:) % Select all elements as a column vector.
  
```

```

%% dimensions
sz = size(A)
size(A,1) % number of rows
size(A,2) % number of cols
length(v) % size of longest dimension
  
```

Plots

```
%% plotting  
t = [0:0.01:0.98];  
y1 = sin(2*pi*4*t);  
plot(t,y1);  
y2 = cos(2*pi*4*t);  
hold on; % "hold off" to turn off  
plot(t,y2,'r--');  
xlabel('time');  
ylabel('value');  
legend('sin','cos');  
title('my plot');  
close; % or, "close all" to close all figs  
  
figure(2), clf; % can specify the figure number  
subplot(1,2,1); % Divide plot into 1x2 grid, access 1st element  
plot(t,y1);  
subplot(1,2,2); % Divide plot into 1x2 grid, access 2nd element  
plot(t,y2);  
axis([0.5 1 -1 1]); % change axis scale
```


Rapid Code Iteration

- Rapid code iterations using cells in the editor
- cells are small sections of code performing specific tasks
- they are separated by double %
- they can be executed independently, eg, CTRL+Enter and their parameters adjusted
- navigate by CTRL+SHIFT+Enter or by jumping
- publish in HTML or PDF or Latex.

Outline

1. Course Organization
2. Getting Started
3. Solving Linear Systems

Systems of Linear Equations

How many solutions have these linear systems? Find it out using the graphical approach.

$$6x - 10y = 2$$

$$3x - 4y = 5$$

% plot functions in implicit form
`ezplot`

$$3x - 4y = 5$$

$$6x - 8y = 10$$

$$3x - 4y = 5$$

$$6x - 8y = 3$$


Systems of Linear Equations

$$6x - 10y = 2$$

$$3x - 4y = 5$$

% plot functions in implicit form
`ezplot('6*x-10*y=2',[0 10 0 10]),`
`hold,`
`ezplot('3*x-4*y=5',[0 10 0 10])`

has one single solution




$$3x - 4y = 5$$

$$6x - 8y = 10$$

`ezplot('3*x-4*y=5',[0 10 0 10]),`
`hold,`
`ezplot('6*x-8*y=10',[0 10 0 10])`

has infinite solutions




$$3x - 4y = 5$$

$$6x - 8y = 3$$

`ezplot('3*x-4*y=5',[0 10 0 10]),`
`hold,`
`ezplot('6*x-8*y=3',[0 10 0 10])`

has no solution



Matrix Form

The linear system:

$$2x_1 + 9x_2 = 5$$

$$3x_1 - 4x_2 = 7$$

can be expressed in vector-matrix form as:

$$\begin{bmatrix} 2 & 9 \\ 3 & -4 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} 5 \\ 7 \end{bmatrix}$$

In general, a set of m equations in n unknowns can be expressed in the form $\mathbf{Ax} = \mathbf{b}$, where \mathbf{A} is $m \times n$, \mathbf{x} is $n \times 1$ and \mathbf{b} is $m \times 1$.

The inverse of \mathbf{A} is \mathbf{A}^{-1} and has property that

$$\mathbf{A}^{-1}\mathbf{A} = \mathbf{A}\mathbf{A}^{-1} = \mathbf{I}$$

Hence the solution to our system is:

$$\mathbf{x} = \mathbf{A}^{-1}\mathbf{b}$$

Inverse and Determinant

Compute the **inverse** and the **determinant** of this matrix in Matlab:

```
>> A=[3 -4; 6 -8];
```

Has the system solutions?

What about the system in the previous slide? What are its solutions?

A matrix is singular if $\det(\mathbf{A}) = |\mathbf{A}| = 0$

Inverse of a square matrix \mathbf{A} is defined only if \mathbf{A} is nonsingular.

If \mathbf{A} is singular, the system has no solution

```
>> A=[3 -4; 6 -8];  
>> det(A)  
ans =  
    0  
>> inv(A)  
Warning: Matrix is singular to working precision.  
ans =  
    Inf Inf  
    Inf Inf
```

Calculating the inverse

$$\mathbf{A}^{-1} = \frac{1}{|\mathbf{A}|} \text{adj}(\mathbf{A})$$

$\text{adj}(\mathbf{A})$ is the adjugate matrix of \mathbf{A} :

1. Calculate the (i, j) minor of \mathbf{A} , denoted \mathbf{M}_{ij} , as the determinant of the $(n-1) \times (n-1)$ matrix that results from deleting row i and column j of \mathbf{A} .
2. Calculate the cofactor matrix of \mathbf{A} , as the $n \times n$ matrix \mathbf{C} whose (i, j) entry is the (i, j) cofactor of \mathbf{A}

$$\mathbf{C}_{ij} = (-1)^{i+j} \mathbf{M}_{ij}$$

3. set $\text{adj}(\mathbf{A})_{ij} = \mathbf{C}_{ji}$

For a 2×2 matrix the matrix inverse is

$$\mathbf{A} = \begin{bmatrix} a & b \\ c & d \end{bmatrix} \quad \mathbf{A}^{-1} = \frac{1}{|\mathbf{A}|} \begin{bmatrix} d & -c \\ -b & a \end{bmatrix}^T = \frac{1}{ad - bc} \begin{bmatrix} d & -b \\ -c & a \end{bmatrix}$$

For a 3×3 matrix

$$\mathbf{A} = \begin{bmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{bmatrix}$$

the matrix inverse is

$$\mathbf{A}^{-1} = \frac{1}{|\mathbf{A}|} \begin{bmatrix} + \begin{vmatrix} a_{22} & a_{23} \\ a_{32} & a_{33} \end{vmatrix} & - \begin{vmatrix} a_{21} & a_{23} \\ a_{31} & a_{33} \end{vmatrix} & + \begin{vmatrix} a_{21} & a_{22} \\ a_{31} & a_{32} \end{vmatrix} \\ - \begin{vmatrix} a_{12} & a_{13} \\ a_{32} & a_{33} \end{vmatrix} & + \begin{vmatrix} a_{11} & a_{13} \\ a_{31} & a_{33} \end{vmatrix} & - \begin{vmatrix} a_{11} & a_{12} \\ a_{31} & a_{32} \end{vmatrix} \\ + \begin{vmatrix} a_{12} & a_{13} \\ a_{22} & a_{23} \end{vmatrix} & - \begin{vmatrix} a_{11} & a_{13} \\ a_{21} & a_{23} \end{vmatrix} & + \begin{vmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{vmatrix} \end{bmatrix}^T$$

Left Division Method

- $\mathbf{x} = \mathbf{A}^{-1}\mathbf{b}$ rarely applied in practice because calculation is likely to introduce numerical inaccuracy
- The inverse is calculated by LU decomposition, the matrix form of Gaussian elimination.

% left division method

$\mathbf{x} = \mathbf{A} \backslash \mathbf{b}$

$$\begin{aligned}\mathbf{A} &= \mathbf{LU} \\ \mathbf{PA} &= \mathbf{LU}\end{aligned}$$

$$\begin{bmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{bmatrix} = \begin{bmatrix} l_{11} & 0 & 0 \\ l_{21} & l_{22} & 0 \\ l_{31} & l_{32} & l_{33} \end{bmatrix} \begin{bmatrix} u_{11} & u_{12} & u_{13} \\ 0 & u_{22} & u_{23} \\ 0 & 0 & u_{33} \end{bmatrix}$$

- Overview to MATLAB programming, environment and arrays
- Solving linear systems in MATLAB
- Work at the posted exercises in small groups

- for a matrix \mathbf{A} , $n \times n$, $\det(\mathbf{A}) \neq 0 \Leftrightarrow$ rank of \mathbf{A} is n
 - for a system $\mathbf{Ax} = \mathbf{b}$ with m equations and n unknowns a solution exists iff $\text{rank}(\mathbf{A}) = \text{rank}([\mathbf{A}\mathbf{b}]) = r$
 - if $r = n \rightsquigarrow$ unique
 - if $r < n \rightsquigarrow$ infinite sol.
 - for a homogeneous system $\mathbf{Ax} = \mathbf{0}$ it is always $\text{rank}(\mathbf{A}) = \text{rank}([\mathbf{A}\mathbf{b}])$ and there is a nonzero solution iff $\text{rank}(\mathbf{A}) < n$
- $\mathbf{A} \setminus \mathbf{b}$ works for square and nonsquare matrices. If nonsquare ($m < n$) then the system is undetermined (infinite solutions). $\mathbf{A} \setminus \mathbf{b}$ returns one variable to zero
- $\mathbf{A} \setminus \mathbf{b}$ does not work when $\det(\mathbf{A}) = 0$.

```
>> A=[2, -4,5;-4,-2,3;2,6,-8];
>> b=[-4;4;0];
>> rank(A)
ans =
     2
>> rank([A,b])
ans =
     2
>> x=A\b
Warning: Matrix is singular to working
precision.
x =
NaN
NaN
NaN
```

However since

$$\text{rank}(\mathbf{A}) = \text{rank}([\mathbf{A}\mathbf{b}])$$

an infinite number of solutions exist (**undetermined system**).

$\mathbf{x} = \text{pinv}(\mathbf{A})\mathbf{b}$ solves with pseudoinverse and $\text{rref}([\mathbf{A},\mathbf{b}])$ finds the reduced row echelon form

Overdetermined Systems

An overdetermined system is a set of equations that has more independent equations than unknowns ($m > n$).

For such a system the matrix inverse method will not work because the A matrix is not square.

However, some overdetermined systems have exact solutions, and they can be obtained with the left division method $x = A \setminus b$

For other overdetermined systems, no exact solution exists. We need to check the ranks of A and $[Ab]$ to know whether the answer is the exact solution. If a solution does not exist, the left-division answer is the least squares solution.

Flowchart for Linear System Solver

