

# E-R Model

Rolf Fagerberg

DM505, Spring 2006, 4th Quarter

# E-R Model

The Entity-Relationship Model:

[Chen, 1976]

- Conceptual data model widely used in DB area.
- Simple:
  - **Entities** ( $\sim$  objects).
  - **Relationships** between entities ( $\sim$  tuples of entities).
  - Entities and relationships can have **attributes** (simple types/domains: integers, strings, booleans...).
- Graphical version: **E-R diagrams**.
- There are standard ways to convert to relational model (discussed later).

Note: different variations of E-R model exist.

# Further Details of the E-R Model

- Key of entity set (minimal)
- Candidate key, primary key
- Arity of relationships
- Roles

Key constraints:

- One-to-one, one-to-many (many-to-one), many-to-many.

Participation Constraints:

- Total participation, partial participation.

# Advanced Concepts in the E-R Model

- Weak entity sets
- ISA hierarchies (inheritance)
- Aggregations

# Notes

- Data modeling is a way of expressing our perception of the world. **Our choices are definitions.**
- Goals:
  - Capture as many aspects of real world as possible.
  - Avoid redundancy.
  - Avoid weak entity sets. Do not be afraid of creating IDs for entities if necessary.
- It takes practice to do well.
- There can be several (good) solutions.
- E-R model (or any other model) cannot capture all semantics.
- Other data models can be used (e.g. UML, or modeling directly in the relational model).